

# System configurations and diagrams

Cable routing in different backplane configurations

The Lenovo logo is positioned in the top right corner of the slide. It consists of the word "Lenovo" in a white, sans-serif font, oriented vertically. The text is set against a rectangular background that features a vertical color gradient, transitioning from a light green at the top to a light blue at the bottom.

Lenovo

## New Lenovo RAID/HBA adapter system configurations

Click the buttons to see the new Lenovo RAID/HBA adapter cable routing in different backplane configurations on different servers.

SR630 V2:

Four  
3.5-inch drive

Eight  
2.5-inch drive

SR650 V2:

Eight  
3.5-inch drive

12  
3.5-inch drive

12 3.5-inch +  
two 3.5-inch  
rear drive

12 3.5-inch +  
four 3.5-inch  
rear drive

Eight  
2.5-inch drive

16  
2.5-inch drive


# SR630 V2 - Four 3.5-inch drive

Three cables:

- One backplane power —
- One x4 SAS/SATA —
- One SuperCap —
  - Two potential locations depending on the CPU heatsink

Optional M.2 backplane or 7 mm rear drive backplane

- Not connected to the HBA/RAID adapter




# SR630 V2 - Eight 2.5-inch drive

Three cables:

- One backplane power —
- One x8 SAS/SATA —
- One SuperCap —
  - Two potential locations depending on the CPU heatsink

Optional M.2 backplane or 7 mm rear drive backplane

- Not connected to the HBA/RAID adapter






# SR650 V2 – Eight 3.5-inch drive

Three cables:

- One backplane power —
- One x8 SAS/SATA —
- One SuperCap —

Optional M.2 backplane or 7 mm rear drive backplane

- Not connected to the HBA/RAID adapter




# SR650 V2 – 12 3.5-inch drive

Four cables:

- One backplane power —
- One x8 SAS/SATA —
- One x4 SAS/SATA —
- One SuperCap —

Optional M.2 backplane or 7 mm rear drive backplane

- Not connected to the HBA/RAID adapter








## SR650 V2 – 12 3.5-inch and two 3.5-inch rear drive

Six cables:

- Two backplane power —
- One x8 SAS/SATA —
- Two x4 SAS/SATA (front and rear) —
- One SuperCap —

Optional M.2 backplane or 7 mm rear drive backplane

- Not connected to the HBA/RAID adapter






## SR650 V2 – 12 3.5-inch and four 3.5-inch rear drive

Six cables:

- Two backplane power —
- One x8 SAS/SATA —
- Two x4 SAS/SATA (front and rear) —
- One SuperCap —

Optional M.2 backplane or 7 mm rear drive backplane

- Not connected to the HBA/RAID adapter






# SR650 V2 – Eight 2.5-inch drive

Three cables:

- One backplane power —
- One x8 SAS/SATA —
- One SuperCap —

Optional M.2 backplane or 7 mm rear drive backplane

- Not connected to the HBA/RAID adapter



# SR650 V2 – 16 2.5-inch drive

Three cables:

- One backplane power —
- One x8 SAS/SATA —
- One SuperCap —

Optional M.2 backplane or 7 mm rear drive backplane

- Not connected to the HBA/RAID adapter

